

ProCash 3000

Monofunctional deposit system
for lobby installations



Bulk deposits of
up to 50 notes

Optimized cash
management

Minimum
footprint

Designed for use
by people with
disabilities

Intelligent
cash and check
deposits

Comprehensive
security
solutions

Open hardware
and software
architectures

Project-specific
solutions



Technical Data

ProCash 3000

DISPLAY

Various VGA, SVGA and XGA resolutions implemented on one display via autoscaling

- 8 stainless steel softkeys
- Touchscreen
- 12.1" TFT LCD
- 15" TFT LCD
- Sunlight TFT LCD
- Privacy display filter

KEYBOARD

- Numeric PIN pad with 4 function keys
- Encrypting PIN pad (EPP V5) with 4 function keys
- PIN shield (VISA-compliant)

CARD HANDLING

- Dip hybrid card reader
- Motorized hybrid card reader
- EMV 2000-certified
- Card retracted if not removed
- Card returned if power fails
- Various card retract compartments

SECURITY

- Intruder alarm
- Portrait camera
- Uninterruptible power supply
- Tamperproof card slot
- Antiskimming device
- Anti-Lebanese loop card reader

SAFES

- UL 291 Level 1
- CEN III / VdS / CNPP
- CEN IV

PRINTERS

- Receipt printer (dot matrix or thermal)
- Journal printer (dot matrix or thermal)

BARCODE READER

- Able to read and process various barcode formats

BANKNOTE PROCESSING

- Mode
 - Cash deposits
- Input of bundles of up to 50 notes (unsorted)
- Up to 2 cassettes (sealable)
- Max. filling height per cassette: 215 mm
- Cassettes with lock
- Separate compartment for counterfeits
- Separate compartment for retracts
- Banknote validation in compliance with ECB article 6
- Metal detection

CHECK PROCESSING

- Input of bundles of up to 50 checks (unsorted)
- Up to 2 cassettes (sealable)
- Max. filling height per cassette: 215 mm
- Cassettes with lock
- Scanner module for single or bundled checks
 - MICR (E13B or CMC7)
 - OCR image processing

MARKETING FEATURES

- Illuminated logo panel
- Optical indicators (MEIs) at all input/output modules
- Info panel for card symbols

AUDIO

- Loudspeakers
- Headset jack

OPERATING SYSTEM

- Windows XP

POWER SUPPLY

110 – 120 V~/220 – 240 V~, 50 – 60 Hz

ENVIRONMENTAL CONDITIONS

TEMPERATURE RANGE

- +5°C to +40°C

RELATIVE HUMIDITY

- 5% to 85%

INSTALLATION

- Frontload
- Rearload
- Indoors

APPROVALS

