

ProCash 3100xe

Multifunction cash recycling system
for lobby installations



Bulk deposit/
dispensing of
up to 400 notes

Optimized cash
management

Flexible
configuration
options


Broad range of
installation
versions

Intelligent
cash and check
deposits

Comprehensive
security
solutions

Open hardware
and software
architectures

Project-specific
solutions



Technical Data

ProCash 3100xe

DISPLAY

Various VGA, SVGA and XGA resolutions implemented on one display via autoscaling

- 8 stainless steel softkeys
- Touchscreen
- 12.1" TFT LCD
- 15" TFT LCD
- Privacy display filter

KEYBOARD

- Numeric PIN pad with 4 function keys
- Encrypting PIN pad (EPP V5) with 4 function keys
- PIN shield (VISA-compliant)
- Alphanumeric/EPP combi keyboard

CARD HANDLING

- Motorized hybrid card reader
- EMV 2000-certified
- Card retracted if not removed
- Card returned if power fails
- Preparatory kit for CIM 06 or MM
- Various card retract compartments

SECURITY

- Intruder alarm
- Portrait camera
- Cash slot camera
- Uninterruptible power supply

- Tamperproof card slot
- Antiskimming device
- Anti-Lebanese loop card reader
- Banknote staining technology

SAFES

- UL 291 Level 1
- CEN L
- CEN III / VdS / CNPP
- CEN IV

PRINTERS

- Receipt printer (dot matrix or thermal)
- Journal printer (dot matrix or thermal)

COIN PROCESSING (SIDECAR)

- Coin dispensing
 - 8 coin hoppers
- Coin deposits

BARCODE READER

- Able to read and process various barcode formats

BANKNOTE PROCESSING

- Modes
 - Cash dispensing
 - Cash deposits
 - Cash deposits/dispersing
 - Cash recycling

- Input of bundles of up to 400 notes (unsorted)
- Output of bundles of up to 99 notes
- Up to 7 cassettes (sealable)
- Up to 5 drum modules for recycling.
- Max. filling height per cassette: 310 mm
- Cassettes with lock
- Cassette presetting
- Separate compartment for counterfeits
- Separate compartment for retracts
- Banknote validation in compliance with ECB article 6
- Metal detection in the input tray

ENVELOPE DEPOSITS

- Integrated envelope dispensing
- Transaction data printed in one line
- Capacity: Up to 200 envelopes, depending on filling

CHECK PROCESSING:

- Input of bundles of up to 50 checks (unsorted)
- Deposit box
- Scanner module for single or bundled checks
 - MICR (E13B or CMC7)
 - OCR image processing

MARKETING FEATURES

- Illuminated logo panel
- Optical indicators (MEIs) at all input/output modules
- Info panel for card symbols

AUDIO

- Loudspeakers
- Headset jack

OPERATING SYSTEM

- Windows XP

POWER SUPPLY

110 – 120 V~/220 – 240 V~, 50 – 60 Hz

ENVIRONMENTAL CONDITIONS

TEMPERATURE RANGE

- +5°C to +40°C

RELATIVE HUMIDITY

- 5 % to 85 %

INSTALLATION

- Frontload
- Rearload
- Indoors

APPROVALS

